

# BOPP Tape Coating Machine

## — Technical Parameters:

Web Width Range	800 – 1600mm
Machine Speed	150 – 250 m/min
Coating Speed	100 – 200 m/min
Unwind and Rewind Diameter	Φ800mm – Φ1000mm

★Design & Production are available for special specifications.

**WEIJIN** 



No. 9-1-1 Hsin Min Lane,  
Chen Ping Li, Nan-Tun Dist., Taichung City, 40871 Taiwan  
TEL: 886-4-2479-0562 FAX: 886-4-2479-3203  
E-mail: [weijin@ms21.hinet.net](mailto:weijin@ms21.hinet.net) <http://www.weijin.com.tw>  
偉晉機械工業有限公司 台中市南屯區鎮平里新民巷9-1-1號

**WEIJIN**   
[www.weijin.com.tw](http://www.weijin.com.tw)



— Applications:

For BOPP Tape

— Outstanding Features:

**A. Machine Mechanism**

1. High speed runs with steady status and low noise.
2. Pneumatic control impression roller – Easy to operate both up & down.
3. Easy operating models for promoting the working efficiency.
4. High efficient drying system.
5. Double layer drying system with adjustable temperature controls make efficient drying possible.
6. Drying System: Steam type, Thermal Oil type, Gas type, Electric drying type.

**B. Electro Control System**

1. Main & sub transmission system are fully micro-computerized PLC programmed & controlled.



2. Man/Machine interface controller with simple, easy to use operator controls.
3. Advanced drive system provides superior web tension control, requires less maintenance, and reduce waste.
4. Easy and quick troubleshooting.
5. Main/auxiliary motor synchronous control system.

***You also can choose these options as below***

1. Optional the Auto Ink Viscosity Control system for accurately predominating the adhesive viscosity.
2. Optional the Auto Thickness Controller for promoting the products quality.
3. Optional the Corona Treatment to increase the material surface adhesion.

**WE ARE**

1. Suitable Industry: Flexible Packaging, Shrink Sleeve, Optical-Electronics Transfer Products.